

Smart way to save; Money and Time!
Smart way to save; Money and Time!

AD-SERVO 30135



- %72 energy saving with servo hydraulic system. Less part cost with eco friendly technology. Noiseless bending with 63 dba. 200 mm/sec bending speed and 5,6 times better synchronization in high speed bends.

Advantages

- Less Energy Consumption
- High Productivity
- Green Machine

Technical Data

Bending Force	135 ton
Bending Length	3.050 mm
Distance Between Columns	2.600 mm
Stroke	265 mm
Daylight	530 mm
Working Height	900 mm
Approach Speed	200 mm/sec
Return Speed	200 mm /sec
Bending Speed	10 mm/sec
Back Gauge X Axis Range	750 mm
Back Gauge R Axis Range	250 mm
Back Gauge Z Axis Range	2050 mm

Motor Specification

Motor Quantity	2 pieces
Motor Type	Servo
Motor Power	2x4

Machine Dimensions

Lenght	4.200 mm
Witdh	1.680 mm
Height	2.750 mm
Weight	10.500 kg

Tool Holder Data

Top Tool Holder	WILA HD NSCL-II-HC/UPB-STL
Bottom Tool Holder	WILA NSCR II-HC-CNC/UPB
Crowning	Motorized

Control Unit

CNC	DA-66T
Screen	15" Touch Panel

Safety System

Front SafetySystem	AKAS 3P M
Back Safety System	Light Barrier